

# ELECTRO-LUBER SERIES

GAS-DRIVEN LUBRICANT DISPENSER – 50 PSI

# ULTIMATE SERIES

MOTOR-DRIVEN LUBRICANT DISPENSER – 900 PSI

# TITAN SERIES

MOTOR-DRIVEN CARTRIDGE LUBRICANT DISPENSER – 900 PSI

# JACK SERIES

MOTOR-DRIVEN JACKSCREW LUBRICANT DISPENSER – 175 PSI



COMPARE AT A GLANCE	ELECTRO-LUBER SERIES	ULTIMATE SERIES	TITAN SERIES	JACK SERIES
<b>APPLICATION</b>	Single Point	Single or Multi-point (up to 12 points)	Single or Multi-point (up to 12 points)	Single or Multi-Point (up to 12 points)
<b>SIZES</b>	Available in 2, 4, 8, or 16 oz. capacity (60, 125, 250 or 475cc)	Available in 4, 8, or 17 oz. capacity (125, 250 or 500cc)	Requires 1 or 2 - 14oz. grease cartridge. Oiler has 47 oz. capacity	Available in 4 oz. capacity (125cc)
<b>TECHNOLOGY</b>	Safe, Inert Nitrogen gas powered	Powerful mechanical fixed-displacement pump	Powerful mechanical fixed-displacement pump. Proven Ultimate Series technology	Powerful mechanical fixed-displacement pump. Jackscrew mechanism incorporated with proven Ultimate Series technology
<b>DISPENSING POWER</b>	Up to 50 psi. Can be remote mounted up to 3 ft	Up to 900 psi. Can be remote mounted up to 30 ft	Up to 900 psi. Can be remote mounted up to 30 ft	Over 175 psi. Can be remote mounted up to 20 ft
<b>POWER SOURCE</b>	AA Alkaline Batteries	Battery pack or remote AC/DC power	Battery pack or remote AC/DC power	Battery pack or remote AC/DC power
<b>CYCLE</b>	Single use, Disposable	Refillable with standard grease gun or pump	Refillable with standard grease cartridge(s). Oiler refillable through screened port	Reusable motor drive unit and easily replaceable single-use cartridge
<b>LUBE CHOICE</b>	Customer specified lube	Customer Fill/Refill	Customer Fill/Refill	Customer specified lube
<b>OPERATING SPAN</b>	14 days to 1 year on factory filled unit	Refilled as needed. Variable from 14 days to 2 years	Cartridge replaced or oiler refilled as needed. Variable from 14 days to 2 years	Cartridge replaced as needed. Variable from 14 days to 2 years
<b>LED INDICATORS</b>	Positive verification unit is working	Tri-color LEDs to indicate normal operation, low battery, low temp.	Tri-color LEDs indicate normal operation, low battery, low lube level, low temp. Oiler has low lube indicator.	Tricolor LEDs indicate normal operation, low battery, low temp
<b>WEATHERPROOF</b>	Waterproof (Submerged) to 30 ft Temp range -40°F to 131°F (-40°C to 55°C) Weathercap available	Suitable for outdoor use in temp range 5°F to 132°F (-15°C to 55°C) Weathercap available	Suitable for outdoor use in temp range 5°F to 132°F (-15°C to 55°C) Weathercap available for cannister and control unit.	Suitable for outdoor use in temp range -40°F to 140°F (-40°C to 60°C) Weathercap available
<b>DISPENSING RATE</b>	Established flowrates, simply select and install	Standard timed intervals or custom programming available	Standard timed intervals or custom programming available	Standard timed intervals or custom programming available
<b>APPROVALS</b>	UL & CUL approved Intrinsically Safe for all areas; MSHA, Energy Mines Canada BAS00ATEX 1228X/1 Approval	UL Division 2 Approval in Process Atex Approval in Process	UL Division 2 Approval in Process Atex Approval in Process	UL Division 2 Approval in Process Atex Approval in Process

TOLL FREE PHONE: 1-800-663-8141

TOLL FREE FAX: 1-800-663-8140

BUS: (604) 946-1308 FAX: (604) 946-0427

www.atselectrolube.com